



SPECIFICATIONS – BARK COLLECTION

Supply of **FAP ceramiche** porcelain stoneware floor tiles.

Product and process features

FAP unglazed porcelain stoneware wall and floor tiles, vitrified full body with added feldspar, quartz and kaolin, obtained by pressing (450 kg/cm² and above) the atomised body and then sintering at a temperature of approx. 1250 °C.
 The full vitrification of the tiles ensures an average absorption of 0.08%, well below the level set in European standard ISO 10545-3.
 The product is therefore compact, frost-proof, resistant to knocks and physical and chemical aggression, bending and differences in temperature.

Conformity to standards ISO 13006 - EN 14411, Annex G

The **BARK** collection complies with all ISO 13006 and EN 14411 standards (Annex G Group Bla E_b ≤0,5%).

Green certifications

FAP ceramiche is a member of the U.S. Green Building Council. LEED compliant, the **BARK** collection can help to obtain between 1 and 7 LEED credits, depending on the colour and use.

Commercial product description

COMPANY	FAP ceramiche
COLLECTION	BARK
SIZES (cm)	25X150 RT, 15X90 RT, 7,5X30
THICKNESS (mm)	10 mm– 8,5 mm (7,5x30)
FINISHES	Matt R9/Atelier R10

